

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (currently amended): A protective screen for screening off a suction space and a suction duct connected to it, in an emergency cooling system of a nuclear power plant, said protective screen including:

at least one screen wall element having a suction side and an outflow side,
wherein the screen wall element is built up of one or more modular rectangular cassette units and

wherein the cassette units each contain
a plurality of screen pockets which are open towards the suction side,
spaced apart walls and one or more intermediate walls arranged between the
spaced apart walls,

which intermediate walls are formed as double walls allowing fluid flow inside
the double walls,

and bent perforated wall segments disposed between the spaced apart walls and
the intermediate walls, said bent perforated wall segments spanning the distance between
adjacent intermediate walls and the spaced apart wall and an intermediate wall, in order to form
the screen pockets, ~~said~~ and wherein the screen pockets having lateral sides and being are
surrounded by outflow gaps, said outflow gaps being connected to the outflow side or open
towards the outflow side,

and wherein the cassette units are configurable for placement in a row in order to
assemble the screen wall element in the desired size.

2. (cancelled):

3. (previously presented): A protective screen in accordance with claim 1,
wherein the screen pockets are each surrounded on their lateral sides by outflow gaps.

4. (previously presented): A protective screen in accordance with claim 1, wherein the bent perforated wall segments are bent in a substantially U-shaped form.

5. (previously presented): A protective screen in accordance with claim 1, wherein the screen pockets have a depth of greater than 0.1 m.

6. (previously presented): A protective screen in accordance with claim 1, wherein the spaced apart walls of the cassette units are formed as double walls having outflow gaps.

7. (previously presented): A protective screen in accordance with claim 1, wherein the spaced apart walls and the intermediate walls of the cassette units are clamped against one another by means of connection elements.

8. (currently amended): A protective screen in accordance with claim 1, wherein any of the spacings between the spaced apart walls and intermediate walls is determined in part by spacer elements disposed between the spaced apart walls and intermediate walls.

9. (currently amended): A protective screen in accordance with claim 1, wherein any of the spaced apart walls or intermediate walls or the perforated and bent wall segments are manufactured from perforated sheet metal.

10. (previously presented) A protective screen in accordance with claim 1, wherein the suction pockets have a depth of greater than 0.2 m.

11. (currently amended) A protective screen in accordance with claim 1, wherein any of the spacings between the two sides of a double wall is determined by spacer elements disposed between the two sides of the double wall.

12. (new) A protective screen in accordance with claim 1, wherein any of the spacings between the intermediate walls is determined by spacer elements disposed between the intermediate walls.